

SAFETY DATA SHEET CLEENOL THICK BLEACH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CLEENOL THICK BLEACH

Internal identification 062392X5, 062400 Container size 2x5L, 12x750ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Highly active thick bleach with added viscosity, allowing the bleach to cling to the surface for

longer, providing more effective cleaning.

1.3. Details of the supplier of the safety data sheet

Supplier Cleenol Group Ltd

> Neville House Beaumont Road Banbury

Oxon OX16 1RB

UK

Tel: +44 (0)1295 251721 sales@cleenol.co.uk

1.4. Emergency telephone number

Emergency telephone In case of a medical emergency following exposure to a chemical, call NHS Direct in England

or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Met. Corr. 1 - H290

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318

Environmental hazards Aquatic Acute 1 - H400

2.2. Label elements

Hazard pictograms





Signal word Danger

Hazard statements H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H400 Very toxic to aquatic life.

CLEENOL THICK BLEACH

Precautionary statements P234 Keep only in original packaging.

P260 Do not breathe vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see medical advice on this label).

P363 Wash contaminated clothing before reuse. P390 Absorb spillage to prevent material damage.

P391 Collect spillage. P405 Store locked up.

P406 Store in a corrosion-resistant container with a resistant inner liner.
P501 Dispose of contents/ container in accordance with national regulations.

Contains SODIUM HYPOCHLORITE, SOLUTION ... % CI ACTIVE, ALCOHOLS, C12-14,

ETHOXYLATED, SULFATES, SODIUM HYDROXIDE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SODIUM HYPOCHLORITE, SOLUTION ... % CI ACTIVE

4.37%

CAS number: 7681-52-9 EC number: 231-668-3 REACH registration number: 01-

2119488154-34-XXXX

M factor (Acute) = 10

Classification

Skin Corr. 1B - H314 Eye Dam. 1 - H318 Aquatic Acute 1 - H400

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES

1-5%

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412

SODIUM HYDROXIDE

<1%

CAS number: 1310-73-2 EC number: 215-185-5 REACH registration number: 01-

2119457892-27-XXXX

Classification

Skin Corr. 1A - H314 Eye Dam. 1 - H318

CLEENOL THICK BLEACH

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention if symptoms are severe or

persist.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink.

Keep affected person under observation. Get medical attention if any discomfort continues.

Skin contact Remove contaminated clothing. Rinse immediately with plenty of water. Get medical attention

if irritation persists after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation The product is not believed to present a hazard due to its physical nature. Prolonged or

repeated exposure may cause the following adverse effects: Irritation.

Ingestion Corrosive. May cause chemical burns in mouth, oesophagus and stomach. May cause

stomach pain or vomiting.

Skin contact Causes severe burns. Prolonged contact causes serious tissue damage.

Eye contact Corrosive. May cause serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use foam, carbon dioxide or dry powder to extinguish.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours.

Hazardous combustion Ther

products

Thermal decomposition or combustion products may include the following substances: Toxic

gases or vapours. Chlorine. Hydrogen chloride (HCI). Oxides of carbon.

5.3. Advice for firefighters

Protective actions during

firefighting

Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

CLEENOL THICK BLEACH

Environmental precautions Collect and place in suitable waste disposal containers and seal securely. Do not discharge

into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if safe to do so. Flush away spillage with plenty of water. Absorb spillage with non-

combustible, absorbent material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Do not use sawdust or other combustible material. Provide adequate ventilation. Flush contaminated area

with plenty of water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with

skin, eyes and clothing. Avoid inhalation of vapours and spray/mists. Do not mix with acid.

Advice on general occupational hygiene

Good personal hygiene procedures should be implemented. Do not eat or drink while using this product. Provide eyewash station. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse. Use appropriate skin cream to

prevent drying of skin.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from

light. Store away from the following materials: Acids. Store at temperatures between 5°C and

25°C. Keep out of the reach of children.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

CLEENOL THICK BLEACH

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). Rubber (natural, latex). To protect hands

from chemicals, gloves should comply with European Standard EN374.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Hygiene measures Good personal hygiene procedures should be implemented. Wash hands and any other

contaminated areas of the body with soap and water before leaving the work site. Use

appropriate skin cream to prevent drying of skin.

Respiratory protection Respiratory protection not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Viscous liquid.

Colour Clear liquid. Yellow.

Odour Citrus. Chlorine.

Odour threshold Not applicable.

pH (concentrated solution): >11

Flash point This product does not sustain combustion.

Relative density ~ 1.07 @ 20°C

Solubility(ies) Soluble in water.

Viscosity 300 - 450 cP @ 20°C

Explosive propertiesThere are no chemical groups present in the product that are associated with explosive

properties.

Comments Information given is applicable to the product as supplied.

9.2. Other information

Other information No further information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The reactivity data for this product will be typical of those for the following class of materials:

Acids. Alkalis. Oxidising materials.

10.2. Chemical stability

Stability Decomposes over time. Factors that increase the rate of decomposition: elevated

temperature, certain metallic impurities, high initial concentration, fall in pH below 11,

exposure to light.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Contact with acids liberates toxic gas.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

CLEENOL THICK BLEACH

Materials to avoid Acids. Ammonia. Organic compounds. Some metals (nickel, iron, copper).

10.6. Hazardous decomposition products

Hazardous decomposition

Chlorine. Hydrogen chloride (HCI). Oxides of chlorine. Hypochlorous acid. Sodium chlorate.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

SECTION 12: Ecological information

Ecotoxicity The product contains a substance which is very toxic to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Harmful to Aquatic Organisms

12.2. Persistence and degradability

Persistence and degradability The product contains inorganic substances which are not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be

considered.

Disposal methods Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1760

UN No. (IMDG) 1760

UN No. (ICAO) 1760

UN No. (ADN) 1760

14.2. UN proper shipping name

Proper shipping name

CORROSIVE LIQUID, N.O.S. (SODIUM HYPOCHLORITE, AMINES, C12-14

(ADR/RID) ALKYLDIMETHYL, N-OXIDES)

Proper shipping name (IMDG) CORROSIVE LIQUID, N.O.S. (SODIUM HYPOCHLORITE, AMINES, C12-14

ALKYLDIMETHYL, N-OXIDES)

CLEENOL THICK BLEACH

Proper shipping name (ICAO) CORROSIVE LIQUID, N.O.S. (SODIUM HYPOCHLORITE, AMINES, C12-14

ALKYLDIMETHYL, N-OXIDES)

Proper shipping name (ADN) CORROSIVE LIQUID, N.O.S. (SODIUM HYPOCHLORITE, AMINES, C12-14

ALKYLDIMETHYL, N-OXIDES)

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID classification code C9

ADR/RID label 8

IMDG class 8

ICAO class/division 8

ADN class 8

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group

ICAO packing group

ADN packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-B

ADR transport category 3

Emergency Action Code 2X

Hazard Identification Number 80

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

CLEENOL THICK BLEACH

National regulations The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as

amended).

EU legislation Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list

of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and

Directive 91/689/EEC on hazardous waste with amendments.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March

2004 on detergents (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products (as amended). Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

work (as amended).

Guidance EH40/2005 Workplace exposure limits

Containing the list of workplace exposure limits for use with the Control of Substances

Hazardous to Health Regulations 2002 (as amended)

Health and Safety Executive

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Regulatory Chemist

Revision date 19/05/2020

Revision 18

 Supersedes date
 29/10/2019

 SDS number
 10363

Hazard statements in full H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.